AUSTRALIAN ANTARCTIC TERRITORY
ROSS DEPENDENCY – ANTARCTICA

SEQUENCE HILLS

SS 55–57, 4 WELCOME MOUNTAIN

SS 55–57, 8 1 : 250,000



REFERENCE

- U.S. & N.Z. Astronomical Station
- U.S. Tellurometer Station (occupied)
- U.S. Intersected Station
- N.Z. Astronomical Station
- Trig Station
- Intersected or resected points
- Principal points of trimetrogen aerial photographs
- Mission & Run — Mission 4A Run 3
- Ice-free land
- Ice covered land
- Glaciers
- Ridge lines
- Glacier front
- Moraine, Scree
- Crevassed areas
- Icefalls
- Cliffs or bluffs
- Coastline definite
- Coastline indefinite
- Height in Metres — 3500
- Routes taken by field parties

LOCALITY DIAGRAM

Ross Dependency boundary shown



Sheet lines based on I.M.W. series.

SCALE

1 : 251,704 at 73° 30′ S. Lat.

Statute Miles: 10 0 10 20

Kilometres: 10 0 10 20 30 40

Nautical Miles: 10 0 10 20

PROJECTION

Polar Stereographic with Scale 1 : 250,000 at standard parallel 71° S. Lat.

Crown Copyright Reserved

Published by the Dept., of Lands & Survey, N. Z.
under the authority of R. P. Gough, Surveyor General.

R. E. Owen, Government Printer, Wellington, New Zealand.

COMPILATION

Compiled from ground surveys by:
New Zealand Geological & Survey Antarctic Expedition (1962–1963)
(Northern Party)
Leader: H. S. Gair
Surveyor: J. A. Tobin

and aerial photography:
Aerial photography supplied by U.S. Geological Survey and flown by U.S. Navy Vx–6 Squadron.

RELIABILITY

The positions of U.S. Geological Survey tellurometer traverse stations, established in 1961-62 in terms of Camp Area datum (Lat. 77° 50′ 52″·5 Long. 166° 40′ 13″·7) have been adopted for overall control purposes.

(1) N.Z. control stations have been fixed by astro observations and triangulation, adjusted to agree with one another and with the U.S.G.S. tellurometer traverse stations. Other points have been fixed by intersecting rays and photo theodolite panoramas from these control stations.

Additional details of ice formation and land form have been obtained from photo-theodolite panoramas and from U.S. aerial photography.

Heights have been determined by theodolite and aneroid barometer, checked against barometric readings supplied by support aircraft, and, where necessary, adjusted to agree with the heights of U.S.G.S. ellurometer traverse stations (datum: Mean sea level, McMurdo).

(2) Detail from U.S. aerial photography based on available limited control.

RELIABILITY DIAGRAM

1ST EDITION
JAN 1966

Refer to this map as:—
NZMS 166
SHEET
SS 55–57, 8