GREENLAND 1:250,000

EDITION 1–AMS

FREDERICK E HYDE FJORD

REFER TO THIS MAP AS: NU 25, 26, 27, 28, 29, 30-1

SERIES C501

5989247

SERIES C501
SHEET NU 25, 26, 27, 28, 29, 30-1
EDITION 1–AMS

U. S. ARMY TOPOGRAPHIC COMMAND

LEGEND

POPULATED PLACES
- Over 1,000 — GODTHAAB
- 750 to 1,000 — HOLSTEINSBORG
- 500 to 750 — FREDERIKSHAAB
- 250 to 500 — Godhavn
- Less than 250 — Christianshaab

ROADS
- Loose surface, graded, all weather
- Loose surface, dry weather, or dirt
- Trail

BOUNDARIES
- Landsdel
- Kommune

Landmark feature
Horizontal control point
Astronomic position
Spot elevation in meters
Landplane airport
Landing area
Seaplane airport
Seaplane anchorage
Glacier
Glacial moraine
Rocks: Awash; Sunken
Wrecks: Exposed; Sunken
Limit of danger; Reef
Foreshore flat
Depth curves in fathoms

C501
Edition 1–AMS (First Printing, 3-57)

Prepared by the Army Map Service (AM), Corps of Engineers, U. S. Army, Washington, D. C. Compiled in 1953 from: AF Preliminary Base, 1:250,000, ACIC, Charts 8 B II, and 9 A II, 1948. Planimetric detail revised by photo-planimetric methods.

Names data was taken directly from Danish sources, except that q Q has been used for ᴙ. K or ᴙ. K.

Universal Transverse Mercator grid, based upon a northward extension of the 6° zones, added by AMS, 1957

GLOSSARY

Bjerg, Bjerge	mountain (s)	Hav	sea
Bugt	bay	Kap	cape
Elv	stream	-skrænten	slope
Fjeld, Fjelde	mountain (s)	-tinde, Tinder	peak (s)
Gletscher	glacier	Ø	island

USERS NOTING ERRORS OR OMISSIONS ON THIS MAP ARE URGED TO MARK HEREON AND FORWARD DIRECTLY TO COMMANDING OFFICER, U. S. ARMY MAP SERVICE, WASHINGTON, D. C. MAPS SO FORWARDED WILL BE RETURNED OR REPLACED IF DESIRED.

Scale 1:250,000

25 Statute Miles
35 Kilometers
15 Nautical Miles

INTERVAL OF APPROXIMATE CONTOURS 200 METERS
WITH SUPPLEMENTARY CONTOURS AT 100 METER INTERVALS
RELIEF PARTIALLY SHOWN BY FORM LINES AND HACHURES
POLAR STEREOGRAPHIC PROJECTION
BLUE NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID ZONES 25 AND 26. INTERNATIONAL SPHEROID
THE LAST FOUR DIGITS OF THE GRID NUMBERS ARE OMITTED
1955 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 51°30′ WESTERLY FOR THE CENTER OF THE WEST EDGE TO 40°15′ WESTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 19′ EASTERLY.

GRID ZONE DESIGNATION:
SHOWN IN BLACK
100,000 M. SQUARE IDENTIFICATION
SHOWN IN BLUE



IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number; example: 92700000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: SPOT ELEVATION 1060

1. Read letters identifying 100,000 meter square in which the point lies: EN
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself: 2
   Estimate tenths from grid line to point: 6
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself: 7
   Estimate tenths from grid line to point: 4

SAMPLE REFERENCE: EN2674

If reporting beyond 10° in any direction, prefix Grid Zone Designation, as: 25YEN2674

PRINTED BY U. S. ARMY MAP SERVICE, CORPS OF ENGINEERS, 3-57 , 777449

FOREIGN SET

U.S. ARMY MAP
G3380s 250 .U5

FREDERICK E HYDE FJORD, GREENLAND