U. S. ARMY
TOPOGRAPHIC COMMAND

C501
Edition 1-AMS

Prepared by the Army Map Service (AMCI), Corps of Engineers, U. S. Army, Washington, D.C. Compiled in 1952 from: USAF Preliminary Base, 1:250,000, ACIC, Charts 109 A III, 109 A IV, 1949. Planimetric detail partially revised by photo-planimetric methods.
Names data was taken directly from Danish sources, except that q Q has been used for ᴙ, K or ᴙ, K.

LEGEND

POPULATED PLACES
- Over 1,000 — GODTHAAB
- 750 to 1,000 — HOLSTEINSBORG
- 500 to 750 — FREDERIKSHAAB
- 250 to 500 — Godhavn
- Less than 250 — Christianshaab

Landplane airport
Landing area
Seaplane airport
Seaplane anchorage
Spot elevation in meters — .75y

Landmark feature
Horizontal control point
Astronomic position
Glacier
Glacial moraine

ROADS
- Loose surface, graded, all weather
- Loose surface, dry weather, or dirt
- Trail

BOUNDARIES
- Landsdel
- Kommune

Rocks: Awash; Sunken
Wrecks: Exposed; Sunken
Limit of danger; Reef
Foreshore flats
Depth curves in fathoms — Mud

GLOSSARY

Isblink	icefield	Sund	sound
Nunatakker	nunataks	Ø	islands

Scale 1:250,000

5 0 5 10 15 20 Statute Miles
5 0 5 10 15 20 25 30 Kilometers
5 0 5 10 Nautical Miles

INTERVAL OF APPROXIMATE CONTOURS 200 METERS.
RELIEF PARTIALLY SHOWN BY FORM LINES AND HACHURES.

TRANSVERSE MERCATOR PROJECTION

BLUE NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID. ZONE 22. INTERNATIONAL SPHEROID

1952 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 42°19' WESTERLY FOR THE CENTER OF THE WEST EDGE TO 47°00' WESTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 8°00' EASTERLY.

USERS NOTING ERRORS OR OMISSIONS ON THIS MAP ARE URGED TO MARK HEREON AND FORWARD DIRECTLY TO COMMANDING OFFICER, ARMY MAP SERVICE, WASHINGTON, D. C. MAPS SO FORWARDED WILL BE RETURNED OR REPLACED IF DESIRED.

LOCATION DIAGRAM FOR NP 21, 22-8



RELIEFABILITY DIAGRAM



No vegetation exists on this sheet.

A. Medium scale aeronautical charts, compiled 1949. Planimetry revised from 1947 aerial photography.

12-64 PRINTED BY 569TH ENGR CO (TOPO) (CORPS)

GRID ZONE DESIGNATION: 22V

100,000 M. SQUARE IDENTIFICATION

EQ	FQ
EP	FP

6EQ 6FQ
6EQ 6FQ

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number; example: 680000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: KANGIGDLERMIUT

1. Read letters identifying 100,000 meter square in which the point lies: EQ
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself: Estimate tenths from grid line to point: 2 3
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself: Estimate tenths from grid line to point: 6 4

SAMPLE REFERENCE: EQ2364

If reporting beyond 9°N-S or 18°E-W, prefix Grid Zone Designation, as: 22VEQ2364

FOREIGN SER.
U.S. ARMY MAP
G8380s 250 .U5
STOCK NO. C501XNP21228

KUÁNIT, GREENLAND