NUNATAKKEN

EDITION 1-AMS

NQ 25, 26-1
AMS SERIES C501

AMS C501
Edition 1-AMS

Prepared by the Army Map Service (AM), Corps of Engineers, U. S. Army, Washington, D. C. Compiled in 1952 from: Large scale maps of Greenland, 1950; Grønland, 1:250,000, Geodætisk Institut, Sheets 67 O. 1, 1941; 67 O. 2, 1937; USAF Preliminary Base, 1:250,000, ACIC, Chart 86 A II, 1949; and intelligence data to 1952. Planimetric detail partially revised by photo-planimetric methods. Names data was taken directly from Danish sources, except that q Q has been used for ϰ, K̄ or ϰ̄, K̄.

GLOSSARY

Bjerge	mountains	Kap	cape
Bugt	bay	Pynt	point
Fjord	fjord	Sund	sound
Holme	islets	Ø	island

LEGEND

POPULATED PLACES
- Over 1,000 — GODTHAAB
- 750 to 1,000 — HOLSTEINSBORG
- 500 to 750 — FREDERIKSHAAB
- 250 to 500 — Godhavn
- Less than 250 — Christianshaab

Landplane airport
Landing area
Seaplane airport
Seaplane anchorage
Spot elevation in meters — 786

Landmark feature
Horizontal control point
Astronomic position
Glacier
Glacial moraine

ROADS
- Loose surface, graded, all weather
- Loose surface, dry weather, or dirt
- Trail

BOUNDARIES
- Landsdel
- Kommune

Rocks: Awash; Sunken
Wrecks: Exposed; Sunken
Limit of danger; Reef
Foreshore flats
Depth curves in fathoms

Rock
Sand
Mud

Scale 1:250,000

5 0 5 10 15 20 Statute Miles
5 0 5 10 15 20 25 30 Kilometers
5 0 5 10 Nautical Miles

CONTOUR INTERVAL 200 METERS
RELIEF PARTIALLY SHOWN BY FORM LINES AND HACHURES

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 25. INTERNATIONAL SPHEROID

THE LAST FOUR DIGITS OF THE GRID NUMBERS ARE OMITTED

1950 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 42°00' WESTERLY FOR THE CENTER OF THE WEST EDGE TO 39°45' WESTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 0°10' EASTERLY.

USERS NOTING ERRORS OR OMISSIONS ON THIS MAP ARE URGED TO MARK HEREON AND FORWARD DIRECTLY TO COMMANDING OFFICER, ARMY MAP SERVICE, WASHINGTON, D. C. MAPS SO FORWARDED WILL BE RETURNED OR REPLACED IF DESIRED.

LOCATION DIAGRAM FOR NQ 25, 26-1



RELIABILITY DIAGRAM



No vegetation exists on this sheet

A. Large scale topographic maps, compiled, 1937-41
B. Medium scale topographic maps, compiled, 1946
C. Medium scale aeronautical chart, compiled, 1949
Planimetry revised from 1947 aerial photography

PRINTED BY ARMY MAP SERVICE, CORPS OF ENGINEERS, 1-54 , 765600

GRID ZONE DESIGNATION: 25W

100,000 M. SQUARE IDENTIFICATION

CR	DR	ER
CQ	DQ	EQ

40 50

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figures of the grid number; example: 74 0000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: ANGMALOKUJUGTOQ

1. Read letters identifying 100,000 meter square in which the point lies: DQ
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself: 8
   Estimate tenths from grid line to point: 8
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself: 6
   Estimate tenths from grid line to point: 4

SAMPLE REFERENCE: DQ8864

If reporting beyond 18° in any direction, prefix Grid Zone Designation, as: 25WDQ8864

NUNATAKKEN, GREENLAND

U. S. ARMY TOPOGRAPHIC COMMAND

U. S. ARMY TOPOGRAPHIC COMMAND

U.S. ARMY MAP
G3380s 250 .U5 FOREIGN SEL